

SPEED-WATCH

FORKLIFT OVERSPEED ALERT SYSTEM



NEXT PAGE



The Speed-Watch Forklift Overspeed Alert System is specifically designed to warn the operator, supervisors, or surrounding pedestrians of the maximum allowed approaching speed of the forklift. Three distinct speed warning levels can be programmed into the Speed-Watch System that will alert the operator or nearby pedestrians as the speed of the vehicle increases. These warnings include a red LED strobe light for a visual effect, voice emitting speaker for an audible effect, or a combination of the two warnings. The control box with display always shows the traveling speed of the forklift for the operator. The battery powered speed sensor comes paired with the system and is quickly installed using a plastic mounting bracket which is adhered using double-sided tape within the wheel of the forklift. The included paired remote is used to easily program the system with the desired forklift speed warning levels and various voice emitted actions. Forklift speed levels are accurately calculated by the system using the diameter measurement of the forklift wheel, and detecting the number of wheel rotations over a given time. The operating voltage of the control box with display and strobe light is 12 – 48V, and both are easily mounted using the included cables ties and optional 100 lb test magnets.

Speed-Watch Features:

- Program up to three distinct warning levels
- Red LED strobe light for visual warning
- Voice emitting speaker for audible warning
- Control box with display always shows the traveling speed of the forklift
- Paired battery powered speed sensor with easy access to replace battery when required
- 12-48V operating voltage for strobe light and control box with display
- Quick and easy installation with included cable ties and 100 lbs test magnets
- Simple programming instructions with use of paired remote

Speed-Watch Forklift Overspeed Alert System
 SPEEDWATCH-B..... **\$850.00**



SPEED-WATCH

FORKLIFT OVERSPEED ALERT SYSTEM



The sensor mounting bracket is easily mounted to the outside of the wheel hub using the double-sided tape provided within the kit. The sensor then easily clicks within the mounting bracket.



The LED alert light is a combination of speaker and LED alert light that flashes and projects both a tone and voice alert when the speed has been exceeded.

SPEED-WATCH

FORKLIFT OVERSPEED ALERT SYSTEM



The Speed-Watch control box can be mounted using either zip ties or 100 lbs test mounting magnets.



The control box will show the operator the speed of the forklift and the alert settings will trigger once the speed has exceeded those settings.

